



ApeosPort Print 4020SD

A4 Monochrome Printer

Features













High Performance & Productivity

- Fast printing of 40 ppm, with FPOT as fast as 5.9 seconds
- Supports standard media input capacity of 350 sheets and up to a maximum of 900 sheets including 100-Sheet Multipurpose Feeder and optional 550-Sheet Tray
- Easy to connect with built-in Wi-Fi, Ethernet or USB

Security


- Prevents information leakage with Confidential Print function
- Controls access to the Printer functions
- Supports settings to delete temporary data files in memory


Easy Operation

- Two-line display lets you configure and monitor vital system information
- Compatible with Mopria® and AirPrint, you can easily print from mobile devices

Ecology

- Standard two-sided printing saves paper
- Supports ECO mode for easy presetting of features that save paper and toner





Specifications

Printing			
Display	2-line All Points Addressable (APA) monochrome LCD display		
Print Speed: Up to	Black: 40 ppm (A4)		
Time to First Page: As fast as	Black: 5.9 seconds		
Print Resolution	Black: 2400 Image Quality, 600 x 600 dpi		
Memory	256 MB		
Hard Disk	Not Available		
Supplies			
Toner Cartridge Yields (up to)	6,000 -page Black High Yield Cartridge / up to: 20,000 -page Black Extra High Yield Cartridge		
Imaging Unit Estimated Yield: Up to	40000 pages, based on 3 average letter/A4-size pages per print job and ~ 5% coverage		
Cartridge(s) Shipping with Product	3,000 -page Toner Cartridge		
Paper Handling			
Included Paper Handling	100-Sheet Multipurpose Feeder, Integrated Duplex, 150-Sheet Output Bin, 250-Sheet Input		
Optional Paper Handling	550-Sheet Tray		
Paper Input Capacity: Up to	Standard: 350 pages 75 gsm / Maximum: 900 pages 75 gsm		
Paper Output Capacity: Up to	Standard: 150 pages 75 gsm / Maximum: 150 pages 75 gsm		
Media Types Supported	Paper Labels, Card Stock, Plain Paper, Envelopes		
Media Sizes Supported	A6, Oficio, 7 3/4 Envelope, 9 Envelope, JIS-B5, A4, Legal, A5, Letter, B5 Envelope, Statement, C- Envelope, Executive, Universal, DL Envelope, Folio, 10 Envelope		
General Information			
Standard Ports	Ethernet 10/100 Base TX (RJ-45), USB Compatible with USB 2.0 Specification (Type B) , 802.11 b/g/n Wireless		
Noise Level: Operating	53 dBA (Print)		
Specified Operating Environment*1	Humidity: 8 to 80%*2 Relative Humidity, Temperature: 10 to 32°C*3 (excluding faults caused by condensation)		
Size (mm - H x W x D) / Weight (kg)	222 x 368 x 363 mm / 9.3 kg		

^{*1 :} Depending on the paper used, the print quality may be degraded until the temperature and humidity environment just before use and the inside of the printer fit into the installation environment. *2 : When the humidity is 80%, the temperature is 25.5°C or less. *3 : Humidity 45% or less when the temperature is 32°C

Option

Product Name	Product Code
550-Sheet Tray	EL300955

Consumables*1

Product Name	Product Code	Product Life
Black High Yield Use and Return Toner Cartridge*2	CT203550	Up to 6,000 pages
Black Extra High Yield Use and Return Toner Cartridge*2	CT203478	Up to 20,000 pages
Black Extra High Yield Regular Toner Cartridge	CT203524	Up to 20,000 pages
Imaging Unit	CT351280	Up to 40,000 pages

^{*1 :} Average standard page yield value declared in accordance with ISO/IEC 19752.

Notes

Although Use and Return consumables are initially installed, consumables without the single-use term, which may be refilled or remanufactured by you or a third party, are available. For details, please refer to our website.

For more information or detailed product specification, please call or visit us at

FUJIFILM Business Innovation Singapore Pte. Ltd.

20E Pasir Panjang Road #02-21A Mapletree Business City Singapore 117439

Tel.+65-6766-8888

fujifilm.com/fbsg

•FUJIFILM and FUJIFILM logo are registered trademarks or trademarks or

^{*2 :} The Use and Return consumables are sold with at a special price contingent upon customer's agreement to use them only once and return them to us for remanufacturing or recycling. For details, please refer to our website.